



## Megamaster Positioner HL3T technical data



### HL3T Technical Data

maximum load	3
Workbench diameter	1000mm
Range of rotational speed	0-3r/min
Driving mode	Cycloidal worm gear + variable frequency speed control
Flip the Angle	0-105°
The rotation Angle	±180°
Power requirements	380V

Megamaster Positioner includes the frame, flipping mechanism, flipping drive system, rotary mechanism and rotary drive system. Both the flipping shaft and the rotary shaft are driven by a speed reduction motor, and the rotary action is realized with the help of gear transmission.

driven by speed reduction motors, ensuring that the equipment maintains synchronization and stability during operation. The motors are equipped with brake functions, making the equipment not only efficient but also safe and reliable. From an overall structural perspective, the center of gravity of the equipment is within the base range, thus providing excellent anti-overturning capability and adaptability to various working scenarios.



in terms of design details, the flange center is equipped with a through-hole, and the backside has reserved mounting holes for the bracket. This design facilitates the installation of hydraulic rotary joints and brackets, while allowing hydraulic pipes to pass through the through-hole, optimizing the piping layout of the equipment. Additionally, T-shaped grooves are designed in all eight directions of the flange, meeting the installation requirements of fixtures. Furthermore, during later design phases, customized designs can be made according to specific fixture requirements, significantly enhancing the versatility and adaptability of the equipment, providing users with a more flexible and efficient usage experience.

- Operation is flexible and convenient
- Easy to install and debug
- Smooth operation, high safety

Efficient	Improve productivity An effective way to weld quality.
Easy to integrate	Easy to use with other products (Integrate, such as the operator.)
Reliable products	For demanding processing Workshop environment design and manufacturing.

# Metalleco

## Megamaster Positioner HL3T technical data



Headoffice: 3185 Dundas St W, Oakville Ontario Canada L6M 4J4

Phone: +1-514-550-1191

Metalleco US: 350 Terry St, Longmont, Colorado 80501 United States of America


Phone: +1-514-550-1191

Metalleco Japan: JRp Hakata Bldg. 3f, 8-1 Chuogai, Hakata-eki, Hakata-ku, Fukuoka City

Phone: +81-90-9516-0894

# Metalleco

## Megamaster Positioner HL3T technical data



**Metalleco**

### METALLECO INC.

Ship to: 3185 Dundas St W, Oakville Ontario L6M 4J4  
CANADA

Mail to: [nick.xiao@metalleco.ca](mailto:nick.xiao@metalleco.ca)

Phone: +1-514-550-1191

REQUESTED BY	DEPARTMENT	GLACCOUNT
SOURCE		
METALLECO INC.		

### PURCHASE REQUISITION

DATEREQUESTED	SHIPVIA
ORDERBY	DATE

ORDER FROM		
PO#	DATE	<input type="checkbox"/> PREPAID PO

QUANTITY	UNIT	STOCK NUMBER	DESCRIPTION	UNIT COST	TOTAL COST

TOTAL ORDER COST:

VENDOR NOTES



Headoffice: 3185 Dundas St W, Oakville Ontario Canada L6M 4J4

Phone: +1-514-550-1191

Metalleco US: 350 Terry St, Longmont, Colorado 80501 United States of America

Phone: +1-514-550-1191

Metalleco Japan: JRp Hakata Bldg. 3f, 8-1 Chuogai, Hakata-eki, Hakata-ku, Fukuoka City

Phone: +81-90-9516-0894

**Metalleco**